



Figure similar

Article No. : 1FK7043-4CH71-1DG2

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data      |             |
|-----------------------|-------------|
| Rated speed (100 K)   | 4,500 rpm   |
| Number of poles       | 6           |
| Rated torque (100 K)  | 2.6 Nm      |
| Rated current         | 3.3 A       |
| Static torque (60 K)  | 2.90 Nm     |
| Static torque (100 K) | 3.50 Nm     |
| Stall current (60 K)  | 3.30 A      |
| Stall current (100 K) | 4.10 A      |
| Moment of inertia     | 1.000 kgcm² |
| Efficiency            | 90.0 %      |

| Physical constants          |                               |
|-----------------------------|-------------------------------|
| Torque constant             | 0.85 Nm/A                     |
| Voltage constant at 20° C   | 54.0 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 1.20 Ω                        |
| Rotating field inductance   | 13.6 mH                       |
| Electrical time constant    | 11.30 ms                      |
| Mechanical time constant    | 0.49 ms                       |
| Thermal time constant       | 40 min                        |
| Shaft torsional stiffness   | 11,400 Nm/rad                 |
| Net weight of the motor     | 6.0 kg                        |

| Mechanical data          |                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Motor type               | Permanent-magnet synchronous motor                                                                                         |
| Motor type               | High Dynamic                                                                                                               |
| Shaft height             | 48                                                                                                                         |
| Cooling                  | Natural cooling                                                                                                            |
| Radial runout tolerance  | 0.040 mm                                                                                                                   |
| Concentricity tolerance  | 0.08 mm                                                                                                                    |
| Axial runout tolerance   | 0.08 mm                                                                                                                    |
| Vibration severity grade | Grade A                                                                                                                    |
| Connector size           | M23                                                                                                                        |
| Degree of protection     | IP65 and DE flange IP67                                                                                                    |
| Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                                                                       |
| Temperature monitoring   | Pt1000 temperature sensor                                                                                                  |
| Electrical connectors    | Connectors for signals and power rotatable                                                                                 |
| Color of the housing     | Standard (Anthracite RAL 7016)                                                                                             |
| Holding brake            | without holding brake                                                                                                      |
| Shaft end                | Plain shaft                                                                                                                |
| Encoder system           | Encoder IC22DQ: incremental encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + commutation position 11 bits |

| Optimum operating point |           |
|-------------------------|-----------|
| Optimum speed           | 4,500 rpm |
| Optimum power           | 1.2 kW    |

| Limiting data                     |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 9,000 rpm |
| Max. permissible speed (inverter) | 9,000 rpm |
| Maximum torque                    | 10.0 Nm   |
| Maximum current                   | 12.5 A    |

| Recommended Motor Module |          |
|--------------------------|----------|
| Rated inverter current   | 5 A      |
| Maximum inverter current | 15 A     |
| Maximum torque           | 10.00 Nm |