



Figure similar

Article No. : 1FK7044-4CH71-1DH2

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data      |             |
|-----------------------|-------------|
| Rated speed (100 K)   | 4,500 rpm   |
| Number of poles       | 6           |
| Rated torque (100 K)  | 3.0 Nm      |
| Rated current         | 3.9 A       |
| Static torque (60 K)  | 3.75 Nm     |
| Static torque (100 K) | 4.50 Nm     |
| Stall current (60 K)  | 4.35 A      |
| Stall current (100 K) | 5.40 A      |
| Moment of inertia     | 1.620 kgcm² |
| Efficiency            | 91.0 %      |

| Physical constants          |                               |
|-----------------------------|-------------------------------|
| Torque constant             | 0.83 Nm/A                     |
| Voltage constant at 20° C   | 53.0 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 0.81 Ω                        |
| Rotating field inductance   | 10.2 mH                       |
| Electrical time constant    | 12.50 ms                      |
| Mechanical time constant    | 0.44 ms                       |
| Thermal time constant       | 45 min                        |
| Shaft torsional stiffness   | 7,900 Nm/rad                  |
| Net weight of the motor     | 8.0 kg                        |

| Mechanical data          |                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Motor type               | Permanent-magnet synchronous motor                                                                                         |
| Motor type               | High Dynamic                                                                                                               |
| Shaft height             | 48                                                                                                                         |
| Cooling                  | Natural cooling                                                                                                            |
| Radial runout tolerance  | 0.040 mm                                                                                                                   |
| Concentricity tolerance  | 0.08 mm                                                                                                                    |
| Axial runout tolerance   | 0.08 mm                                                                                                                    |
| Vibration severity grade | Grade A                                                                                                                    |
| Connector size           | M23                                                                                                                        |
| Degree of protection     | IP65 and DE flange IP67                                                                                                    |
| Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                                                                       |
| Temperature monitoring   | Pt1000 temperature sensor                                                                                                  |
| Electrical connectors    | Connectors for signals and power rotatable                                                                                 |
| Color of the housing     | Standard (Anthracite RAL 7016)                                                                                             |
| Holding brake            | with holding brake                                                                                                         |
| Shaft end                | Plain shaft                                                                                                                |
| Encoder system           | Encoder IC22DQ: incremental encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + commutation position 11 bits |

| Optimum operating point |           |
|-------------------------|-----------|
| Optimum speed           | 4,500 rpm |
| Optimum power           | 1.4 kW    |

| Limiting data                     |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 9,000 rpm |
| Max. permissible speed (inverter) | 9,000 rpm |
| Maximum torque                    | 13.0 Nm   |
| Maximum current                   | 16.4 A    |

| Holding brake         |                        |
|-----------------------|------------------------|
| Holding brake version | Permanent-magnet brake |
| Holding torque        | 4.0 Nm                 |
| Power supply voltage  | DC 24 V ± 10 %         |
| Coil current          | 0.5 A                  |
| Opening time          | 70 ms                  |
| Closing time          | 30 ms                  |
| Highest braking work  | 150 J                  |

| Recommended Motor Module |          |
|--------------------------|----------|
| Rated inverter current   | 9 A      |
| Maximum inverter current | 27 A     |
| Maximum torque           | 13.00 Nm |