



Figure similar

Article No. : 1FK7064-4CH71-1PA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data      |             |
|-----------------------|-------------|
| Rated speed (100 K)   | 4,500 rpm   |
| Number of poles       | 6           |
| Rated torque (100 K)  | 5.0 Nm      |
| Rated current         | 7.0 A       |
| Static torque (60 K)  | 10.00 Nm    |
| Static torque (100 K) | 12.00 Nm    |
| Stall current (60 K)  | 12.20 A     |
| Stall current (100 K) | 15.00 A     |
| Moment of inertia     | 7.500 kgcm² |
| Efficiency            | 93.0 %      |

| Physical constants          |                               |
|-----------------------------|-------------------------------|
| Torque constant             | 0.80 Nm/A                     |
| Voltage constant at 20° C   | 50.5 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 0.17 Ω                        |
| Rotating field inductance   | 6.2 mH                        |
| Electrical time constant    | 36.50 ms                      |
| Mechanical time constant    | 0.60 ms                       |
| Thermal time constant       | 55 min                        |
| Shaft torsional stiffness   | 29,500 Nm/rad                 |
| Net weight of the motor     | 15.4 kg                       |

| Mechanical data          |                                                                      |
|--------------------------|----------------------------------------------------------------------|
| Motor type               | Permanent-magnet synchronous motor                                   |
| Motor type               | High Dynamic                                                         |
| Shaft height             | 63                                                                   |
| Cooling                  | Natural cooling                                                      |
| Radial runout tolerance  | 0.040 mm                                                             |
| Concentricity tolerance  | 0.10 mm                                                              |
| Axial runout tolerance   | 0.10 mm                                                              |
| Vibration severity grade | Grade A                                                              |
| Connector size           | M23                                                                  |
| Degree of protection     | IP64                                                                 |
| Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                 |
| Temperature monitoring   | Pt1000 temperature sensor                                            |
| Electrical connectors    | Connectors for signals and power rotatable                           |
| Color of the housing     | Standard (Anthracite RAL 7016)                                       |
| Holding brake            | without holding brake                                                |
| Shaft end                | Feather key                                                          |
| Encoder system           | Resolver R14DQ: resolver 14 bits (resolution 16384, internal 2-pole) |

| Optimum operating point |           |
|-------------------------|-----------|
| Optimum speed           | 3,500 rpm |
| Optimum power           | 2.8 kW    |

| Limiting data                     |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 7,500 rpm |
| Max. permissible speed (inverter) | 7,500 rpm |
| Maximum torque                    | 32.0 Nm   |
| Maximum current                   | 46.0 A    |

| Recommended Motor Module |          |
|--------------------------|----------|
| Rated inverter current   | 18 A     |
| Maximum inverter current | 54 A     |
| Maximum torque           | 32.00 Nm |